

## Produktserie Lena Advanced – Industrie

Bezeichnung der Anlage	Leistung, m <sup>3</sup> /hr						Anschlussleistung, W	Anschluss
	Wasser nach Tiefenreinigung (Mebranen/Umkehrosiose)		Grundwasser		Oberflächenwasser			
	UVT = 90%		UVT = 85%		UVT = 70%			
	25 mJ/cm <sup>2</sup>	40 mJ/cm <sup>2</sup>	25 mJ/cm <sup>2</sup>	40 mJ/cm <sup>2</sup>	25 mJ/cm <sup>2</sup>	40 mJ/cm <sup>2</sup>		
DUV-1-48-N ADV	3,2	2	3	1,9	2,2	1,4	52	R 1"
DUV-1-87-N ADV	7,5	4,7	7	4,4	5,1	3,2	95	R 2"
DUV-1A120-N ADV	10	6,3	8	5	5,8	3,6	140	R 2"
DUV-1A250-N ADV	20	13	17	11	12,2	7,7	230	R 2"
DUV-1A350-N ADV	30	19	27	17	19	12	330	R 2"
DUV-1A500-N ADV	50	32	44	28	28	18	440	DN 100
DUV-1A700-N ADV	70	44	61	39	39	24	540	DN 100