

Produktserie Lena Master – Industrie

Bezeichnung der Anlage	Leistung, m ³ /hr						Anschlussleistung, W	Anschluss
	Wasser nach Tiefenreinigung (Membranen/Umkehrosiose)		Grundwasser		Oberflächenwasser			
	UVT = 90%		UVT = 85%		UVT = 70%			
	25 mJ/cm ²	40 mJ/cm ²	25 mJ/cm ²	40 mJ/cm ²	25 mJ/cm ²	40 mJ/cm ²		
DUV-1-48-N MST	3,2	2	3	1,9	2,2	1,4	52	R 1"
DUV-1-87-N MST	7,5	4,7	7	4,4	5,1	3,2	95	R 2"
DUV-1A120-N MST	10	6,3	8	5	5,8	3,6	140	R 2"
DUV-1A250-N MST	20	13	17	11	12,2	7,7	230	R 2"
DUV-1A350-N MST	30	19	27	17	19	12	330	R 2"
DUV-1A500-N MST	50	32	44	28	28	18	440	DN 100
DUV-1A700-N MST	70	44	61	39	39	24	540	DN 100
DUV-2A500-N MST	100	63	82	52	51	32	1 100	DN 100
DUV-2A700-N MST	-	-	115	72	71	45	1 300	DN 100
DUV-3A500-N MST	175	110	143	90	83	52	1 600	DN 150
DUV-4A500-N MST	260	165	210	130	116	73	2 000	DN 200
DUV-5A500-N MST	-	-	268	170	147	92	2 500	DN 200
DUV-5A500-NE MST	360	225	-	-	-	-	2 500	DN 250
DUV-6A500-N MST	-	-	315	200	172	108	2 900	DN 200
DUV-6A500-NE MST	420	265	-	-	-	-	2 900	DN 250
DUV-7A500-N MST	-	-	384	240	207	130	3 400	DN 200